Application Serial No.:

10/582,813

Attorney Docket No:

26068-27B

Examiner: D. Nguyen

Art Unit: 2818

Claims 1-29: (Canceled)

30. (Previously presented) A magnetic bit cell for use in a planar Hall effect magnetoresistive random access memory (MRAM) device, the magnetic bit cell

comprising:

an active area comprising a magnetic film that exhibits both planar Hall effect and

biaxial magnetic anisotropy;

a first pair of conductive leads arranged on opposing sides of the active area for

driving electrical current across the active area in a first direction; and

a second pair of conductive leads arranged on opposing sides of the active area in

a second direction perpendicular to the first direction for measuring voltage across the

active area in the second direction;

wherein the magnetic film is epitaxially grown on a perovskite single crystal so

that easy axes of the thin film are perpendicular to each other and at a 45-degree angle

relative to the direction of the current.

31. (Canceled)

32. (Currently amended) The magnetic bit cell according to claim 30 [[31]], wherein

the magnetic film is deposited on the perovskite crystal in the shape of a cross having arm

portions of approximately equal length, and the first pair of conductive leads and the

second pair of conductive leads are coated on the arm portions of the magnetic film,

wherein a middle portion of the magnetic film is left uncovered by the conductive leads.

33. (Original) The magnetic bit cell according to claim 30, wherein the conductive

leads are copper.

34. (Canceled)

{W1732580;2}

2

Application Serial No.:

10/582,813

Attorney Docket No:

26068-27B

Examiner: D. Nguyen

Art Unit: 2818

35. (Original) The magnetic bit cell according to claim 30, further comprising a first

write bit line and a second write bit line electrically isolated from the magnetic bit cell by

an insulating layer.

36. (Original) The magnetic bit cell according to claim 35, wherein the first write bit

line and the second write bit line are arranged perpendicular to each other.

37. (Withdrawn) The magnetic bit cell according to claim 36, wherein the first write

bit line and the second write bit line overlap each other and are positioned below the

active area of the magnetic bit cell, separated by the insulating layer.

38. (Withdrawn) The magnetic bit cell according to claim 36, wherein the first write

bit line and the second write bit line overlap each other and are positioned above the

active area of the magnetic bit cell, separated by the insulating layer.

39. (Currently amended) The magnetic bit cell according to claim 36, wherein one of

the write bit lines is positioned substantially directly above the active area of the

magnetic bit cell separated from the active area by a first insulating layer and the other

write bit line is positioned substantially directly below the active area of the magnetic bit

cell separated from the active area by a second insulating layer.

40. (Original) The magnetic bit cell according to claim 35, wherein the insulating

layer is an aluminum oxide or strontium titanite.

41. (Original) The magnetic bit cell according to claim 35, wherein the first write bit

line and the second write bit line comprise a conductive film through which current can

be passed.

42. (Original) The magnetic bit cell according to claim 41, wherein a combination of

current in the first write bit line and the second write bit line generates a field that flips

the magnetization between the two easy axes of the magnetic bit cell.

{W1732580;2}

3

Application Serial No.:

10/582,813

Attorney Docket No:

26068-27B

Examiner: D. Nguyen

Art Unit: 2818

43. (Currently amended) The magnetic bit cell according to claim 30 [[31]], wherein

the magnetic film is deposited on the crystal by physical vapor deposition.

44. (Original) The magnetic bit cell according to claim 43, wherein the deposited film

has a thickness between about 4 nm and about 100 nm.

45. (Original) The magnetic bit cell according to claim 44, wherein the deposited film

has a thickness between about 10 nm and about 50 nm.

46. (Original) The magnetic bit cell according to claim 30, wherein the magnetic film

is a manganite thin film of the formula R_{1-x}A_xMnO₃, wherein R is a rare-earth metal, A is

an alkaline earth metal, and x is between about 0.15 and about 0.5.

47. (Original) The magnetic bit cell according to claim 46, wherein the rare earth

metal is lanthanum.

48. (Original) The magnetic bit cell according to claim 46, wherein the alkaline earth

metal is selected from the group consisting of strontium, calcium, and barium.

Claims 49-56: (Canceled)

57. (New) The magnetic bit cell according to claim 42, wherein the sign of the

voltage indicates along which of the two easy axes the magnetization in the bit cell

resides.

{W1732580;2}

4